

ΗΜΙΑΥΤΟΜΑΤΗ ΤΥΛΙΧΤΙΚΗ ΜΗΧΑΝΗ ΠΑΛΕΤΩΝ ΜΕ ΑΝΩ ΠΛΑΚΑ
ΣΥΓΚΡΑΤΗΣΗΣ ΠΑΛΕΤΩΝ PW-1100

Specifications

Specifications	PW-1100 (621)	PW-1100 (631)	PW-1100 (121)	PW-1100 (131)
Pallet load dimensions				
Max. length (mm)	1200	1200	1200	1200
Max. width (mm)	800	800	1000	1000
Max height (mm)	1755	2255	1755	2255
Max. pallet load (kg)	1500	1500	1000	1000
Machine dimensions				
Length (mm)	2615	2615	2680	2680
Width (mm)	1480	1480	1630*	1630*
Height (mm)	2654	3154	2654	3154
Min. height above floor (mm)	125	125	125	125
Film roll dimension (mm)	Length max. 440-520, outer diameter max. 400, inner diameter 76.			
Capacity	Max. 50 pallets per hour.			
Electric specifications	3 x 230/400 V, 50 Hz, power consumption 0.5 kW. Other specifications upon request.			
Surface treatment	All parts are powder-coated or electro-galvanised.			
Colours	Red RAL 2002, black RAL 9005 (available in other colours at a surcharge).			